

DUPLO

	Capacity	Standard Lifting Height	Max Lifting Height	Minimum Platform	Standard Platform	Max Platform	Platform distance	Pit	Power	Speed	Power supply	Standard Weight	Notes
DUPLO 30 T	3.000 kg.	2.190 mm	2.190 mm	2.200x5.200 mm	2.500 x 5.200 mm	2.700x5.200 mm	2.010 mm	2.500 mm	2,5 kw	0,03 m/s	400 v / 50 hz	2.850 kg.	tileable roof, max 70 kg/m ²
	6.608 lbs	86,2 inch	86,2 inch	86.6x204.7 inch	98.4x204.7 inch	106.3x204.7 inch	79,1 inch	79,1 inch	3,4 hp	1,2 inch/s	400 v / 50 hz	6.278 lbs	tiles on the roof up to 70 kg/m ²
DUPLO 25/2	2.500 + 2.500 kg.	2.190 mm	2.190 mm	2.200x5.200 mm	2.500 x 5.200 mm	2.700x5.200 mm	2.100 mm	2.500 mm	2,5 kw	0,03 m/s	400 v / 50 hz	2.850 kg.	two platforms with two cars
	5.510 + 5.510 lbs	86,2 inch	86,2 inch	86.6x204.7 inch	98.4x204.7 inch	106.3x204.7 inch	82,7 inch	79,1 inch	3,4 hp	1,2 inch/s	400 v / 50 hz	6.278 lbs	two platforms for two cars
DUPLO 20/2 T	2.000 + 2.000 kg.	2.190 mm	2.190 mm	2.200x5.200 mm	2.500 x 5.200 mm	2.700x5.200 mm	2.010 mm	2.500 mm	2,5 kw	0,03 m/s	400 v / 50 hz	2.850 kg.	platform + tileable roof with two cars
	4.410 + 4.410 lbs	86,2 inch	86,2 inch	86.6x204.7 inch	98.4x204.7 inch	106.3x204.7 inch	79,1 inch	79,1 inch	3,4 hp	1,2 inch/s	400 v / 50 hz	6.278 lbs	platform + tiles on the roof up to 70 kg/m ²