

MONO

	Capacity	Standard Lifting Height	Max Lifting Height	Minimum Platform	Standard Platform	Max Platform	Pit	Power	Speed	Power supply	Standard Weight	Notes
MONO 7,5	750 kg.	4000 mm	17000 mm	500x840 mm	2000x2500 mm	2000x2500 mm	130 mm	2,5 kw	0,15 m/s	400 v / 50 hz	1150 kg.	The speed changes according the diameter of the hydraulic pistons installed
	1652 lbs	157,5 inch	669,3 inch	19,7x33,1 inch	78,7x98,4 inch	78,7x98,4 inch	5,1 inch	3,4 hp	5,9 inch/s	400 v / 50 hz	2533 lbs	
MONO 10	1000 kg.	4000 mm	17000 mm	500x840 mm	2000x2500 mm	2000x2500 mm	130 mm	2,5 kw	0,15 m/s	400 v / 50 hz	1150 kg.	The speed changes according the diameter of the hydraulic pistons installed
	2203 lbs	157,5 inch	669,3 inch	19,7x33,1 inch	78,7x98,4 inch	78,7x98,4 inch	5,1 inch	3,4 hp	5,9 inch/s	400 v / 50 hz	2533 lbs	
MONO 15	1500 kg.	4000 mm	17000 mm	500x1150 mm	2000x2500 mm	2000x2500 mm	130 mm	2,5 kw	0,13 m/s	400 v / 50 hz	1350 kg.	The speed changes according the diameter of the hydraulic pistons installed
	3304 lbs	157,5 inch	669,3 inch	19,7x33,1 inch	78,7x98,4 inch	78,7x98,4 inch	5,1 inch	3,4 hp	5,1 inch/s	400 v / 50 hz	2974 lbs	