

# HYPERLIFT

	Capacity	Standard Lifting Height	Max Lifting Height	Minimum Platform	Standard Platform	Max Platform	Pit	Power	Speed	Power supply	Standard Weight	Notes
HYPER-LIFT	8000 kg.	4000 mm	14000 mm	3250 x 6000 mm	3250 x 6450 mm	3950 x 7950 mm	600 mm	7,50 kw	0,05 m/s	400 v / 50 hz	6500 kg.	
	17621 lbs	157,5 inch	551,2 inch	128 x 236,2 inch	128 x 254 inch	156 x 315 inch	23,6 mm	10,2 hp	2,0 inch/s	400 v / 50 hz	14317 lbs	
HYPER-LIFT REVERSE GUIDES	8000 kg.	4000 mm	14000 mm	3250 x 6000 mm	3250 x 6450 mm	3950 x 7950 mm	1400 mm	7,50 kw	0,05 m/s	400 v / 50 hz	6500 kg.	
	17621 lbs	157,5 inch	551,2 inch	128 x 236,2 inch	128 x 254 inch	156 x 315 inch	55,1 mm	10,2 hp	2,0 inch/s	400 v / 50 hz	14317 lbs	
HYPERLIFT + TP	5000 kg.	4000 mm	14000 mm	3250 x 6000 mm	3250 x 6450 mm	3950 x 7950 mm	1400 mm	7,50 kw	0,05 m/s	400 v / 50 hz	8500 kg.	
	11013 lbs	157,5 inch	551,2 inch	128 x 236,2 inch	128 x 254 inch	156 x 315 inch	55,1 mm	10,2 hp	2,0 inch/s	400 v / 50 hz	18722 lbs	

## NOTES :

Capacity of 8.000 Kg will be reduced in case of:

- Installation of lateral protections on top of the platform
- Roller shutters on top of the platform

In case the columns will not pop up on the top, pit will be the same of Hyperlift with roof version.