

# REX GOLD

	Capacity	Standard Lifting Height	Max Lifting Height	Minimum Platform	Standard Platform	Max Platform	Useful height	Pit	Power	Speed	Power supply	Standard Weight	Notes
REX 30 GOLD	3000 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm		510 mm	4 kw	0,05 m/s	400 v / 50 hz	4000 kg.	
	6608 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch		20,1 inch	5,4 hp	2,0 inch/s	400 v / 50 hz	8811 lbs	
REX 25 GOLD + T	2500 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5800 kg.	Roof
	5507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12775 lbs	
REX 25 GOLD + TP	2500 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5600 kg.	Roof/ roof with tiles
	5507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12335 lbs	
REX 30 GOLD F	3000 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm		510 mm	4 kw	0,05 m/s	400 v / 50 hz	4100 kg.	F= flanged
	6608 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch		20,1 inch	5,4 hp	2,0 inch/s	400 v / 50 hz	9031 lbs	
REX 25 GOLD F + T	2500 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	6000 kg.	F=flanged Roof
	5507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	13216 lbs	
REX 25 GOLD F + TP	2500 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5800 kg.	F= flanged Roof/ Roof with tiles
	5507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12775 lbs	